PRODUCT SHEET

VÖLVA

MULTINORM PARKA / RAIN JACKET

EN ISO 20471 (2013) + A1 (2016) 3

EN 343 (2019) 4 3 x

EN ISO 11612 (2015) A1, B1, C1, E1, F1

EN 1149-5 (2008)

EN 61482-2 (2020) APC 1

EN 13034 (2005) + A1 (2009) Type PB (6)

EN ISO 11611 (2015) A1 Class 2

PPE CATEGORY 3 WITH ARC PROTECTION CLASS 1



THE + PRODUCTS



PPE for use in ATEX environments.



Removable, lined hood for optimum protection against the elements.



Inner ribbed cuffs.



PARKAVOLV01JM



PARKAVOLV01OM



PARKAVOLV01RM

S to 3XL
Other size, on demand.

40

According to ISO 6330 4N.

Box of 10.
Individual transparent packaging.

FIT & ZIP

SOFTSHELL



PHÉNIX



IBIS

POLAR FLEECE JACKET



SKOLL

PRODUCT DESCRIPTION

- Category 3 high visibility parka with ARC ELECTRIC Class 1 protection.
- Suitable for ATEX environments.
- Flame retardant and antistatic.
- Breathable and waterproof.
- Fully taped seams.
- Ergonomic pre-shaped fitted sleeves.
- Central full plastic zip fastening with double slider, under double protective flap closed with six concealed plastic press studs.
- High collar fastened with three concealed plastic press studs, enclosing a large removable hood.
- Chin strap.
- Double central flap with gutter system for rainwater drainage.
- Two remote microphone brackets for detectors.
- Sleeve cuffs with inside rib cuffs.
- One breast pocket with zip fastening, right-hand when worn. Retractable plastic badge holder, hidden in this pocket.
- Two lower pockets with plastic zips.
- One 'Napoleon' type pocket under the central flap, closed by zip.
- One inside pocket closed by a concealed press stud, on the right front when worn.
- FIT&ZIP system: zip fastening and tabs for attaching a removable T2S multi-risk lining.
- Two RETHIOTEX® 26 535-01 segmented microbead heat-sealed retroreflective half straps.
- Two RETHIOTEX® 26 535-01 segmented microbead retroreflective thermobonded waistbands.
- Two RETHIOTEX® segmented microbead retroreflective armbands heat-bonded to each sleeve.
- Standards pictograms on left sleeve when worn.

RAW MATERIALS

OUTER FABRIC

- 3-layers laminated fabric FR 37% polyester, 12% Protex®, 8% cotton, 2% aramid, 40% PU, 1% AS (275 g/sqm).

RETROREFLECTIVE TRANSFER

- RETHIOTEX® 26 535-01 segmented microbead retroreflective transfer, heat-bonded flame retardant.

COMPLIANCE

Compliance with the essential safety requirements has been verified using the following harmonised standards:

- **EN ISO 13688 (2013) + A1 (2021)** for protective clothing - general requirements.
- **EN ISO 20471 (2013) + A1 (2016)** for high visibility warning clothing.
- **EN 343 (2019)** for protection against rain.
- **EN ISO 11612 (2015)** for clothing to protect against heat and flame.
- **EN 1149-5 (2018)** for protection against electrostatic discharges.
- **EN 61482-2 (2020)** for live working. Protective clothing against the thermal hazards of an electric arc. Part 2: requirements.
- **EN 13034 (2005) + A1 (2009)** for protection against liquid chemicals.
- **EN ISO 11611 (2015)** for protective clothing for use in welding and allied processes.

CUSTOMIZATION

CHEST HEART SIDE





Maximum dimensions:
80 x 50 mm
60 x 60 mm

BACK





Maximum dimensions:
200 x 100 mm
150 x 150 mm

Before going into production, we make a proof of concept from the vector file (vectorised .eps, .ai, .pdf) you send us.

Certain technical requirements may prevent us from printing in the desired location. **OTHER MARKING, PLEASE CONTACT US.**

Paper recycling

02/26/2026 FT DM 1602/02. Photos and texts not contractually binding.

T2S - Z.I. La Vaure - B.P. 20930 - 42290 SORBIERS - FRANCE
+33 (0)4 77 53 05 05
info@t2s.fr
T2S.FR